

GEOCHEMICAL CHARACTERIZATION OF WASTE ROCK

ANTAMINA MINE

PERU

David Brown, Golder Associates
Rens Verburg, Golder Associates
Henri Letient, Antamina
Celedonio Aranda, Antamina

BC/MEND Workshop
November 30, 2005




Presentation Overview

- Site Background
- Waste Rock and Ore
 - Issues
 - Investigation
 - Results
- Ongoing Work and Conclusions


ANTAMINA MINE LOCATION



- Peruvian Andes (4,200m)
- Upper Amazon drainage basin
- Copper-zinc-molybdenum mine
- Full production in 3rd quarter 2001
- Daily tonnage:
 - Ore – ~100,000,
 - Waste - ~300,000
- Mine life of 23 years



Site Overview



Geochemical Issues

- Potential impacts to water quality from
 - Sulfide oxidation
 - Acid generation
 - Metal leaching
 - Dissolution of stored oxidation products
 - Mineral dissolution
 - Metal leaching (under neutral conditions – e.g. Cu, Zn, Mo)

Waste Rock Issues

- Over 1.3 billion tonnes of waste rock, to be distributed in three major dumps
- LG/MG Ore processed year 23 (LOM)
- Operational/post-closure site drainage management

Objectives

- Establish long-term monitoring plan of waste dumps and stockpiles
- Refinement of waste rock classification
- Define operational criteria for waste rock routing
- Optimization of closure requirements and operational/post-closure site drainage management

Gap Analysis

- Significant static geochemical waste rock characterization completed prior to mining
- Samples not always representative of current rock
- Additional information available through pit development
- Develop characterization program to take advantage of exposed rock

Waste Rock Classification

- Three classes: A, B, C
 - A: skarn, intrusive
 - A, B, C: hornfels, marble, limestone
 - Sulfide, zinc, arsenic content
- Current system protective of environment, but refinement feasible

Geochemical Characterization Program

- Static tests
 - Metals, ABA, leach tests (DI, H₂O₂): 100s of samples
- Mineralogy
- Kinetic testing (8 cells)
- Field cells (27 cells)
- Waste rock and LG/MG ore stockpile runoff monitoring

Summary of Field Cells

- 27 Field Cells Constructed (2002 - 2005)
 - Hornfels & Marble
 - Class A – 4 Cells
 - Class B – 7 Cells
 - Class C – 3 Cells
 - Class A Skarn & Intrusives
 - Intrusives – 3 Cells
 - Endoskarn – 2 Cells
 - Exoskarn – 2 Cells
 - LG Ore – 3 Cells
 - MG Ore – 3 Cells



Waste Rock Program Field Cell Construction

- Field cell construction
 - Clean 55-gallon plastic drum
 - Drum placement on terraced and secure area
 - Bottom drainage layer (\approx 15 cm silica sand) overlain by filter fabric




Field Cell Monitoring


- Leachate sample collection
 - Variable sampling frequency
 - monthly during wet season, more frequent at beginning of wet season, and not in dry season
 - Field parameters & laboratory analysis




Rock Field Cell Results Zn (Hornfels & Marble Cells)







Rock Field Cell Results Zn (LG/MG Ore Cells)



Rock Field Cell Results Zn (Intrusives and Skarn Cells)




Zn Field and Lab Cell Results




○ Lab Cell

■ Field Cell


Rock Field Cell Results Mo (LG/MG Ore Cells)



Rock Field Cell Results Mo (Intrusives & Skarn Cells)







Mo Field and Lab Cell Results



○ Lab Cell

■ Field Cell

SO₄Mo Field and Lab Cell Results



○ Lab Cell

■ Field Cell

Water Quality Simulations

- LG/MG ore and waste rock metal release simulated using existing field cell loading rates (supplemented by evaluation of data from laboratory kinetic testing and short-term leach testing)

Water Quality Simulations

- Predictive water quality modelling completed to evaluate potential impacts to the receiving environment from:
 - existing waste rock classes (Life of Mine)
 - potential modifications to waste rock classification system and placement strategies
 - Varying Class A skarn and intrusives content
 - Varying Class A hornfels/marble
 - Varying Class B hornfels/marble content

Water Quality Simulations

Key Findings

- Continued treatment of East Dump and LG/MG ore stockpile drainage
 - Simulated concentrations similar or higher than current levels
- Tucush Dump drainage quality very sensitive to the amount of Class A skarn and intrusive material placed in the dump
 - increase in proportions of Class A skarn and intrusives has adverse impact on water quality in the Tucush drainage
- Varying the Class B material content in the Tucush Dump minimal impact on water quality

Ongoing Work – Waste Rock Classification

- Development of quality control and characterization procedures for waste rock placement
- Continued refinement of the waste rock classification system
- On-going monitoring of field cells
- Instrumentation of test piles ~6,000 tonnes, ~38m x 38m x 10m high (UBC)

Characterization of Other Materials

- Tailings
 - Static testing (metals, ABA, short-term leach)
 - Mineralogy
 - Laboratory and field cell
 - Tailings porewater quality collected from piezometers installed in beach
 - Tailings impoundment pond and seepage water quality monitoring data
- Lake Sediments
 - Static and laboratory kinetic cells

Conclusions

- Importance of initiating this type of program early on in the mine life
- Field cells more reliable than lab tests (if time permits)
- Need for ongoing testing and monitoring
- Water quality prediction based on field cells data used for waste rock management and long term planning



THANK YOU