


Rio Tinto

**Progress in Remediating
ARD-Contaminated
Groundwater at
Bingham Canyon Mine,
Utah, USA**

Kennecott Utah Copper



Presentation Outline

- Nature of Problem
 - Regulatory Framework
 - Containment and Remediation
 - Water Treatment
 - Cleanup Timeframe
 - Questions
- 

Acknowledgements




Rio Tinto


Nature of Problem





Kennecott Utah Copper (KUC) Bingham Canyon Mine








2010 Sulfate Concentrations

-  20,000+ mg/L
-  15,000 - 19,999 mg/L
-  10,000 - 14,999 mg/L
-  5,000 - 9,999 mg/L
-  1,500 - 4,999 mg/L
-  500 - 1,499 mg/L



Rio Tinto

Regulatory Framework



Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- 1986 — EPA begins Preliminary Site Investigation
- 1994 — EPA proposes site for National Priority List (NPL)
- 1995 — Memo of Understanding between EPA, State of Utah, and Kennecott Utah Copper (KUC)
- 1998 — RI/FS completed (*Site Investigation*)
- 2000 — ROD issued (*Approval of Cleanup Plan*)
- 2002 — RDRA completed (*Design and Implementation*)
- 2008 — Consent Decree issued (*Legal Agreement*)
- 2008 — NPL proposal withdrawn

Natural Resource Damage (NRD)

- 1986 — State of Utah files NRD claim for groundwater impacted by ARD
- 1992 — Initial NRD settlement rejected after Jordan Valley Water Conservancy District (JVWCD) intervenes
- 1995 — NRD settlement approved; KUC provides funding to “restore, replace, or acquire equivalent”
- 2004 — State of Utah approves a joint KUC/JVWCD groundwater treatment project
- 2006 — KUC commissions Reverse Osmosis (RO) water treatment plant for Zone A
- 2012 — JVWCD anticipated to open KUC funded RO water treatment plant for Zone B


Remedies Summary

- EPA through CERCLA:
 - Maintain source controls and provide plume containment through pumping
 - Remediate aquifer through pumping and monitored natural attenuation (MNA)
 - Treat extracted groundwater and dispose of treatment residuals
- State of Utah through NRD:
 - Construct and operate a RO water treatment plant for Zone A
 - Fund construction of RO water treatment plant for Zone B to be owned and operated by JWCD
 - Each plant to produce 3,500 acre-feet/year for 40 years

Rio Tinto

Containment and Remediation






2010 Sulfate Concentrations

- 20,000+ mg/L
- 15,000 - 19,999 mg/L
- 10,000 - 14,999 mg/L
- 5,000 - 9,999 mg/L
- 1,500 - 4,999 mg/L
- 500 - 1,499 mg/L

Extraction Wells

- Acidic Extraction Well
- Sulfate Extraction Wells
- New Sulfate Extraction Well
- JWCD Extraction Wells





7 16 '92







08 15 08






Acidic Extraction Wells

	ECG1146	BSG1201	BSG2784
Installed	1995	2003	2008
Material	Stainless Steel	Stainless Steel	Stainless Steel
Diameter	18-inch	18-inch	18-inch
Total Depth	760 ft bgs	752 ft bgs	870 ft bgs
Screen Intervals	500-700 ft bgs	500-740 ft bgs	490-600 ft bgs 700-850 ft bgs
Static Water Level	390 ft bgs	460 ft bgs	420ft bgs
Pumping System	200 HP SS Submersible	200 HP SS Submersible	200 HP SS Submersible
Average Pumping Rate	670 gpm	620 gpm	620 gpm
Production 5 Year Rolling Average	2,100 to 2,600 acre-feet/year		

Sulfate Extraction Wells

	BFG1200	B2G1193	LTG1147
Installed	2001	1998	1995
Material	Stainless Steel	Stainless Steel	Carbon/Stainless
Diameter	18-inch	18-inch	16-inch
Total Depth	820 ft bgs	1,070 ft bgs	605 ft bgs
Screen Intervals	420-800 ft bgs	450-1060 ft bgs	400-590 ft bgs
Static Water Level	420 ft bgs	450 ft bgs	420 ft bgs
Pumping System	350 HP SS Submersible 350 HP Booster	350 HP SS Submersible 350 HP Booster	200 HP SS Submersible 250 HP Booster
Average Pumping Rate	1,400 gpm	1,500 gpm	400 gpm
Production 5 Year Rolling Average	3,500 to 3,800 acre-feet/year		

RioTinto




Rio Tinto

Water Treatment



Pump and Treat Strategy



Reverse Osmosis Treatment Plant

Configuration	Two X 2-stage skids
Membranes	Hydranautics ESPA2 (Spiral Wound Polyamide)
Pressure Vessels	Protec and CodeLine
Feed Rate	3,000 gpm to Membranes
Recovery Rate	71 to 74%
Remineralization	200 gpm
Production Rate	2,400 gpm
Production Goal	3,500 acre-feet/year





Tailings Line Management Criteria

- Compliance point is the North Splitter Box (located north of the Copperton Concentrator)
- Neutralization potential (NP) in a given month should be either; greater than or equal to the Copperton Concentrator tailings NP, OR at least 5 t CaCO₃ eq/kt
 - Evaluated as a six-month rolling average
- Aqueous alkalinity should be greater than or equal to 10 mg CaCO₃ eq/L at least 90% of the time
 - Evaluated as a six-month rolling average
- Aqueous pH should be greater than or equal to 6.7 at least 90% of the time
 - Evaluated per calendar year







DTI
S
MENT
TH
E

SPG 10/1 1/2 1/2 1/2

Rio Tinto

Cleanup Timeframe




Column Leaching Tests and Geochemical Modeling Summaries

- Performed in 1990's as part of the RIFS process to:
 - Evaluate remedial options and assist with designing remedial pumping network
- Column Leaching Tests:
 - Approximately 40 pore volumes, equivalent to approximately 800 years
- Geochemical Modeling:
 - Five different models were developed to evaluate lime demand, with a total of 9 different simulations
 - Extrapolation column data, extrapolation of data from complete recovery wells, expanded 1D geochemical model, empirical rinse curve model, and an extended 1D advection-dispersion model with mass extraction

RioTinto

Calculated Lime Demand



Rio Tinto

Questions

