

24<sup>th</sup> ANNUAL BRITISH COLUMBIA-MEND ML/ARD WORKSHOP

# Challenges and Best Practices in Metal Leaching and Acid Rock Drainage

Simon Fraser University, Vancouver, November 29 and 30, 2017

## Waste Rock Inclusions to Improve the Performance of Tailings Impoundments: The Canadian Malartic Case Study

**Michel Aubertin**, ing. Ph.D.

Professor Emeritus, Polytechnique Montreal

Executive Director, Canadian Geotechnical Society ([www.cgs.ca](http://www.cgs.ca))

[michel.aubertin@polymtl.ca](mailto:michel.aubertin@polymtl.ca)



POLYTECHNIQUE  
MONTREAL

LE GÉNIE  
EN PREMIÈRE CLASSE



# Content

- Introduction
- Use of waste rock inclusions (WRI)
  - Drainage and consolidation
  - Geotechnical stability
  - Other aspects
- CRD Project at Canadian Malartic Mine
- Discussion
- Final remarks



*In collaboration with Michael James, Bruno Bussière, Thomas Pabst (RIME), Normand D'Anjou, Carl Pednault (CM), Nicolas Pépin, Marielle Limoges (Golder), and many students*



# IRME-RIME

## UQAT-POLYTECHNIQUE

Institut de recherche en mines et environnement  
Research Institute of Mines and Environment

<http://rime-irme.ca/en>



POLYTECHNIQUE  
MONTRÉAL



LE GÉNIE  
EN PREMIÈRE CLASSE



**RioTinto**

MINE RAGLAN  
UNE COMPAGNIE GLENCORE

# Mine Wastes Management

- **Many challenges related to chemical and physical (geotechnical) stability**
- **Various types of environmental impacts**
- **Waste rock and tailings usually managed separately; co-disposal offers different options**





# Tailings impoundments and waste rock piles

## Hard rock mine tailings

Cohesionless;  
Low plasticity (ML or SM-ML)  
Compressible, low strength;  
Low hydraulic conductivity



## Waste Rock

Coarse grained;  
Stiff and strong,  
Pervious

James 2012



(Aubertin et al. 1991, 2002, 2013; Bussière, 2007; James et al. 2011, 2013, 2017)



# TSF historical failures worldwide

(Davies, 2002; Aubertin et al. 2002, 2011; Azam and Li 2010; [www.wise-uranium.org](http://www.wise-uranium.org), 2017)

- 5 major events/yr in '60,70 & 80s
- 2 major events/yr in 1990s and 2000+
- **Little improvement over last 25 years.**
- TSF still highly prone to failure; rates ~ 10 X higher
- Mainly during mine operation (> 80%).
- Upstream dikes represent more than 90% of cases.







Independent Expert Engineering Investigation and Review Panel

# Report on Mount Polley Tailings Storage Facility Breach

Morgenstern, Vick, Van Zyl, 2015



Samarco; village of  
Bento Rodriguez  
(Brazil 2015)

# Improved disposal with waste rock inclusions (WRI) in tailings impoundment


(Aubertin et al. 2002; James et Aubertin, 2009, 2010, 2012)



- Main considerations:
  - Properties of tailings and waste rock, and interfaces
  - Location and geometry of waste rock inclusions
  - Effect on the geotechnical behaviour (consolidation, stability)




# The Concept of Waste Rock Inclusion



Jaouhar, 2011





WRI : accelerate consolidation;  
Increase overall strength and stability;  
Compartmentalize impoundment;  
Reduces (avoid) WR Piles  
Control the effects of liquefaction:  
Loading on dike; Limit deformation;  
Reduce potential for flow.  
Facilitate closure and reclamation








Somewhat similar to sand drains,  
rock drains, wick drains (Barksdale et al. 1983)




Water flow and horizontal  
drainage due to vertical  
drains (also reinforcement)

Consolidation during filling  
(added layers)



Simulations with SIGMA/W (GeoSlope)



WRI accelerates consolidation  
 (Jaouhar et al. 2011; L. Bolduc et Aubertin, 2913 2914)  
 Effect depends on spacing  
 (and many other factors).



# Seismic behavior (stability) of tailings impoundments

**Liquefaction** due to generation of excess porewater pressure within saturated, contractive, cohesionless media (soils, tailings) under static or dynamic loading, sufficient to reduce the strength (effective stress) near zero (e.g. Kramer, 1996)



Tapo Canyon tailings impoundment USA, Northridge 1994 (adapted NISEE 2003)





Figure 4.4. Carte du Canada montrant les régions sismiques utilisées dans le Code national du bâtiment (2005); tirée de Adams et Halchuk (2004a, 2007).



Las Palmas Tailing dam failure, 2010, Chile (adapted from Bray 2010)



# **Cyclic DSS testing (James 2009) and physical modeling (Shaking Table Tests; Pépin et al. 2012)**




- Signal sinusoidal 1 hz
- 0,12g max
- tests on sand and tailings





Results used for  
Calibrating/validating  
Numerical simulations  
With FLAC and  
UBC-Sand model

# James, 2009; Ferdosi et al., 2014, 2015; FLAC & UBCSand model



No Inclusion



With Inclusions







Figure 4.4. Carte du Canada montrant les régions sismiques utili-  
bâtiement (2005); tirée de Adams et Halchuk (2004a, 2007).  
11111111



# CRD Projet on Waste Rock inclusions 2015-2019 +



In situ measurements with extensive  
characterization and modelling;  
Optimisation of WRI



**AGNICO EAGLE**

MINE RAGLAN  
UNE COMPAGNIE GLENCORE




UQAT-POLYTECHNIQUE  
Research Institute of Mines and Environment



Waste rock inclusion constructed in the tailings impoundment at the Canadian Malartic mine. Such inclusions act as drainage and reinforcement elements to improve the hydro-geotechnical behaviour of the impoundment (photo provided by Osisko).



a)



b)

Figure 3 – a) Photo of the southern part of the Canadian Malartic tailings impoundment with the approximate location of the two new waste rock inclusions (arrows) that will be built for this project; b) Schematic view of the waste rock inclusions in the impoundment

# CRD PROJECT

## INTEGRATED PROGRAM OF:

- Conventional and specialized lab tests
- Physical modelling in the laboratory
- Site observation and monitoring
- Numerical simulation

## COMPONENTS AND TASKS

Material characterization

Interaction between the tailings and waste

Monitoring and data analysis

Numerical simulations (laboratory & field scale)

Optimization strategy and guidelines








# CANADIAN MALARTIC MINE



- Annual production : 580 000 oz of gold
- Daily production of 55 000 tons ore and 180 000 tons waste rock
- Impoundment of 470 hectares (+);  $P > 65\%$
- Expected dike height ~ 40 m
- 6.7 km of perimeter dykes





# MONITORING AND OBSERVATION: PWP, VWC, SETTLEMENTS, $V_s$









# FIELD TESTS AND SITE INVESTIGATION; INTERACTION OF WASTE ROCK AND TAILINGS



Increased Strength (CPT)  
close to WRI  
(Golder, 2013, 2017)

# MATERIAL CHARACTERIZATION – STATIC & CYCLIC LIQUEFACTION

Geotechnical testing with undrained loading (Grimard; Archambault-A. 2017)





# INTERACTION OF WASTE ROCK AND TAILINGS





Physical modelling (Saleh Mbemba, 2015; Essayad, 2017)



**Tailings infiltration**  
**Tailings flow characterization**  
**Drainage capacity**  
**Potential for internal erosion**  
**Effects of macro-porosity**








Seismic  
 Numerical  
 Analyses  
 (Ferdosi et al.  
 2015, 16);  
 Various WRI  
 Configuraitons  
 & Mw




## MAIN ADVANTAGES OF WRI (James et al. 2013)

- ✓ Accelerated drainage and consolidation
- ✓ Denser tailings; more rapid strength gain
- ✓ Reduced susceptibility to liquefaction and erosion
- ✓ Controlled dissipation of post-seismic EPWP
- ✓ Improved static and seismic stability
- ✓ Less material released in the event of a rupture
- ✓ More management options (compartmentalization)
- ✓ Progressive closure of the tailings impoundment
- ✓ Working surface for the placement of a cover
- ✓ Less material in the waste rock pile;
- ✓ Submerged reactive minerals; reduced risk of AMD or CND from the waste rock pile





# LIFE CYCLE OF A TAILINGS IMPOUNDMENT WITH WRI ( James et al. 2017)



Step 1 – Construction of dykes and inclusions

Step 2 – Tailings deposition

Step 3 – Management towards (for) closure

Step 4 – Start closure before end of operations

Step 5 – Ultimate condition (landform)







FIG. 5. The LTA tailings disposal site during the construction of a CCBE made of three layers (adapted from Aubertin et al., 2002)



(Aubertin et al., 1999;  
Dagenais, Ouangrawa,  
Cosset, Pabst,  
Broda, Éthier)



Prevention and Control  
of AMD or CND;  
Closure and reclamation



# Final remarks

- Exist various ways of improving disposal practices to help prevent geotechnical and hydro-geochemical problems
- Ongoing R&D on WRI with industrial partners aims at developing another option to manage tailings and waste rock.
- Various publications on WRI since 2002 (including a few at CGS GeoOttawa 2017)
- Other results to come.





# IRME-RIME

## UQAT-POLYTECHNIQUE

Institut de recherche en mines et environnement  
Research Institute of Mines and Environment

<http://rime-irme.ca/en>



POLYTECHNIQUE  
MONTRÉAL



LE GÉNIE  
EN PREMIÈRE CLASSE

