

#### 22<sup>nd</sup> BC MEND Metal Leaching and Acid Rock Drainage Workshop

December 2 - 3, 2015 Vancouver, British Columbia, Canada

# Closure of a Legacy WRP: Transitioning to Passive Treatment



Greg Meiers Cody Bradley Mike O'Kane Joe Shea



Public Works and Government Services Canada

O'Kane Consultants

Integrated Mine Waste Management and Closure Services Specialists in Geochemistry and Unsaturated Zone Hydrology

#### **Presentation Discussion Points**

- Overarching Project Background
- Background for Focus of this Presentation
  - Reclaimed Victoria Junction Site
- Conceptual Model
  - Physical
  - Flow
  - Geochemical
- Summary
   Discussion
   Points





#### **Background – Site Location**





## **Background – Typical Climate**

- Mean annual PPT is ~ 1,500 mm
- 60% occurs in Winter (October to March)
- ~50% of winter PPT is rainfall
- Mean annual
   *PE* ~700 mm
- Energy deficit in most months



Atmospheric Water Demand In Summer



Meiers et al 2014

#### Background

- ECBC is a Federal Crown Corporation responsible for environmental remediation associated with coal mining activities in Cape Breton
  - Mining operations began in 1685 to the 1980s
  - 50 underground mines produced 500 million tonnes of coal



Meiers et al 2014

Consultants

## Historical Mine Sites: Sydney, N.S.

#### **Remediation:** Enterprise Cape Breton Corporation

**Current Management:** 

- Victoria Junction (VJ)
   Other Reclaimed
   WRPs
- Scotchtown Summit (Summit)
- Franklin
- Lingan
- Dominion No.4
- Gowrie
- Princess



Public Works and Government Services Canada





## **WRP Monitoring System**

- Monitored water balance component:
  - AET
  - PPT
  - Runoff
  - Interflow
  - Water Storage
  - Net Percolation (NP)
- NP Estimated through:
  - Water Balance
  - Analytical Estimates
  - Conservative Tracer
- Internal WRP Monitoring System:
  - Temperature
  - Pressure
  - GW Elevations
  - Pore-Gas Concentrations
  - Pore-Water Quality





#### Meiers et al 2014

## VJ – Site Background

#### Landform:

- Covers an area of 26 ha
- Height of 40m
- Plateau ~7%
- Side Slope 3:1
- Runoff ditch constructed around plateau which channels runoff to drop structures on side slope





#### VJ – Developing Conceptual Model

- Surface Hydrology
- Treatment and collection
- Indicator / Receptor to identify changes to loading to wetland and groundwater

#### Allow for Testing of Geochemical Model



## **VJ – Physical Model**





## **VJ – Physical Model**





#### **VJ – Physical Model**



#### WRP: Waste Rock / Tailings

- TSF No.1 and No.2 relocated to WRP
- TSF No.3 and No.4 covered in 1987
- TSF No.5 active until 1988
- Effect of tailings facilities on WRP drain-down



#### **Surface and GW Flow Model**

- Upward gradient in bedrock drives contaminant plume to surface
- Surface and groundwater contaminant load focused to Monitoring Point VJ ST-2016



## Loading, Collection, and Treatment

Acid Load Mass Balance to

**O'Kane** Consultants

Test Three Conceptual

#### **Progressive changes** to site

operations:

985

quality



#### **Acid Load Phase 1**

#### **Active Treatment Pre-Cover System**

- Flow × Concentration = Load
- NP ~400 mm/yr
- NP and mounding provides the basal seepage
- Water treatment removes ~788 t/yr



#### Managing Load & Cover Systems



## VJ – Managing Load

## Seasonal Changes in Acid load at VJ ST-2016 would support:

Solubility Controlled – Constant Concentration



#### WRP Drain-Down

- Saturated drain-down estimated at 75 mm/yr and will terminate in approximately 20 years
  - Numerical modelling completed to verify rates and inform on *unsaturated drain-down* which *terminate in ~100 years*



#### **Post-Cover System Conceptual Model**

- Reduction in deep groundwater loading
- Upward gradient in bedrock

Water and O<sub>2</sub> Ingress to Pile Mobilization Rate

> Geochem Model Potential and Stored Acidity

> > Drain-down

Upward Gradient in Bedrock

Plunge +17 Azimuth 328

300

**VJ ST-2016** 

**GW Mounding** 

#### Acid Load Phase 2 - Cover & Passive

#### **Post-Cover System with Passive Treatment**

- Total acid load generated reduced from ~934 t/yr to ~38 t/yr
- Approximately 26% of load collected in leachate collection system
- Decommissioned pump-and-treat wells, reduction in treated load from 100 t/yr to 10 t/yr... Why



#### Acid Load Phase 3 – Prediction

#### 100 Years Post-Cover System w/ Passive Treatment

- Mounding contributes largest load
- Total acid load reduced to ~38 t/yr
- Understanding for long-term loading and outcomes without numerical simulations



## Solute Transport (Sulphate)





#### **Risk – Influence of Holes**



Very Good Lateral Drainage Capacity:

… extend timeline

Service Life of Geomembranes?

e.g. Benson et al 2011: 55-125 yrs

O'Kane and Meiers 2014

 Does a product in design carry the risk of failure, or a system



**O'Kane** 

Consultants

#### Costs, Loading, and Risk

Discount Rate (%)	Collection and Treatment NPV	Cover System NPV
1.0	\$ 29.5M	\$ 16.1M
2.5	\$ 17.0M	\$ 14.6M
4.0	\$ 11.2M	\$ 13.8M

Groundwater Collection System Only Captured 40% of Basal Load



#### **Summary Discussion Points**

- Going Back in Time: "Correct" Decision?
  - Depends on what **Discount Rate** you would use...
  - Value in receiving environment...
- More Importantly
  - Stop and think about the number of *Technical Assumptions* within the NPV calculation
    - For example: Flow Reduction = Load Reduction (i.e. constant)
- Is the Level of Information available for this Site Typical?



#### Getting Back to the Question...

 Can we Achieve Passive Treatment to Manage Residual Seepage in the Short Term?

- Strong evidence for it at this site

• What About Other Sites?

- Scale / Size of WRP









O'Kane Consultants Rainbow of Hope for Children and, Habitat for Humanity Initiative



#### Water Balance

- Cover system layering influences surface runoff
- Surface runoff and interflow ~65% for the geomembrane cover systems
- Interflow and NP offsets proportional runoff volume
- NP at Lingan
   ~30%
- High leakage at Summit



#### **Geomembrane Defects**

- Construction (wrinkles, tears, welds, punctures,...)
- Post Construction
  - Service Stress (differential settlement,  $\Delta$  temp)
  - Anthropogenic (e.g. artisanal mining)
  - Bioturbation
  - Vegetation (roots, blow down, etc.)



http://heapsolutions.com/applications/heap-liner-leak-detection/ O'Kane and Meiers 2014



#### **Background – Cover System Profiles**



O'Kane Consultants