




How the Design, Construction and Performance of Permeable Reactive Barriers Keeps Getting Better

BC MEND ML/ARD – Vancouver, BC

December 1, 2022

Kevin E. French, P.Eng.

Presentation Overview



- Introduction
- Overview of ML/ARD & PRBs
- Site Characterization Inputs
- Alignment Profiling
- Remedial Amendments

- Bench-Scale Testing
- Detailed Design & Sensitivity Analysis
- Installation Techniques
- QA/QC Testing
- Closing Thoughts


Introduction



Introduction – Presenter

Kevin French, P.Eng

- Vice President, Vertex Environmental
- B.A.Sc., Civil/Env. Eng., U. Waterloo
- Environmental engineering (consulting and remediation contracting) since 1988



Vertex Environmental Inc.

- Founded in 2003
- Specialized Environmental Remediation Contracting (in-situ, ex-situ, systems, HRSC)
- Provides services across Canada



Background on ML/ARD and PRBs




Background on ML/ARD



- Metal leachate (ML) and acid rock drainage (ARD) are common issues at mine sites where the rock contains reactive sulfide minerals
- Dissolved-phase heavy metal plumes are also common at other industrial sites
- When exposed to air and water, oxidation of the sulfides generates acidity
- The resulting leachate typically has a low pH and high concentrations of soluble heavy metals
- The long-term generation of ML/ARD requires an effective and equally long-term and ideally passive and sustainable solution

Background on PRBs

- Intercept and passively treat contaminated groundwater plumes
- Allow groundwater to flow through unimpeded
- Can be excavated, soil mixed or injected, etc.
- Long-lasting and sustainable (no energy use to operate)
- Contain plumes and prevent off-site migration
- Protect sensitive receptors
- Mitigate regulatory and/or third party liability




How to Design and Install a PRB – Old School



- Use generic assumptions / rules of thumb
- Dig a trench
- Mix up some ZVI and sand
- Maybe do some mag. separation testing
- Backfill the trench
- Hope for the best...
 - Under-design = Failure
 - Over-design = Wasted \$\$
- But what if there is something unusual about your site?
- Is there a better way?


Designing and Installing a PRB – A Better Way



Site Characterization Inputs



Site Characterization Inputs



Basic Requirements (data package):


- Remedial objectives
- Contaminant types & concentrations
- Groundwater field readings
- Plume configuration / dimensions
- Groundwater depth / flow direction
- Groundwater flow velocity estimate
- Stratigraphy / BH logs
- Confining layer / base of plume
- Site access / installation restrictions



Site Characterization Inputs

Added Benefit (detailed CSM):


- 3D contaminant distribution
- Increasing / decreasing / steady state plume
- Seasonal variabilities
- Heterogeneities
- Hydraulic conductivity measurements
- Hydraulic gradients
- Fracture porosity (if bedrock)
- Detailed geochemistry
- Contaminant mass flux estimate



Alignment Profiling



High-Resolution Site Characterization




- Used to better understand subsurface conditions in fine detail
- HRSC tools can detect:
 - Permeability – Hydraulic Profiling Tool (HPT)
 - Electrical Conductivity
 - Other tools can detect LNAPL, PHCs, VOCs
- Available in Canada since 2011
- HRSC has been used at 100s of sites across Canada with 10s of km in depth probed


Source:
Geoprobe Web Site



HRSC Results – HPT vs BH



HRSC Results – Data Visualization



Remedial Amendments



Zero-Valent Iron (ZVI) Background

- Elemental iron (Fe^0)
- Discovered in 1980s; first PRBs installed in 1990s
- Main uses were and remain heavy metals and chlorinated ethylenes
- Mechanisms: chemical reduction, complexation, (co-)precipitation of heavy metals
- Particulate solid: not mobile; will not migrate
- Multiple application techniques
- Inexpensive and readily available
- Well established, long-lasting technology
- Many of these original ZVI PRBs are still active and effective today (proven 20+ years longevity)



ZVI – Metals Treated

Contaminant Removal: Metals and Metalloids (Overview)

Wang et al. 2021. Chemosphere. In press.

Legend:

- Forms Cations
- Forms Oxyanions
- ◻ Redox with ZVI Possible
- ◻ Remediation/Treatment w/ZVI

H																	He
Li	Be											B	C	N	O	F	Ne
Na	Mg											Al	Si	P	S	Cl	Ar
K	Ca	Sc	Ti	V	Cr	Mn	Fe	Co	Ni	Cu	Zn	Ga	Ge	As	Se	Br	Kr
Rb	Sr	Y	Zr	Nb	Mo	Tc	Ru	Rh	Pd	Ag	Cd	In	Sn	Sb	Te	I	Xe
Cs	Ba		Hf	Ta	W	Re	Os	Ir	Pt	Au	Hg	Tl	Pb	Bi	Po	At	Rn
Fr	Ra		Rf	Db	Sg	Bh	Hs	Mt	Ds	Rg	Cn	Nh	Fl	Mc	Lv	Ts	Og
La	Ce	Pr	Nd	Pm	Sm	Eu	Gd	Tb	Dy	Ho	Er	Tm	Yb	Lu			
Ac	Th	Pa	U	Np	Pu	Am	Cm	Bk	Cf	Es	Fm	Md	No	Lr			

Common Metals Treated:

Most multi-valent cations: As, Cd, Co, Cr, Cu, Hg, Mn, Mo, Ni, Pb, Sb, Zn and more



Acidity Buffering Amendments

- Typically carbonate rock (limestone, dolostone, etc.) that is less soluble than CaO or $\text{Ca}(\text{OH})_2$
- Main purpose is to assist in buffering pH and increasing alkalinity
- Not all created equal: different hardness and ABA (Sobek) values (especially pH and NNP)
- Some can also contain other trace metals!
- Must consider particle size, surface area, fines (porosity & buffering capacity over time)
- Particulate solid: not mobile; will not migrate
- More limited application techniques
- Inexpensive and readily available



Bench-Scale Testing



Types of Bench-Scale Tests

Static Batch Reactor Testing:



- Small quantities of waste, soil or groundwater from a site or spiked samples
- Physical, chemical, biological or combinations of testing possible
- Aerobic or anaerobic conditions
- Testing for inorganic or organic contaminants
- Relatively quick, easy and inexpensive to complete

Types of Bench-Scale Tests

Flow-Through Column Reactor Testing:

- Larger quantities of groundwater from a site or spiked samples
- Physical, chemical, biological or combinations of testing possible
- Aerobic or anaerobic conditions
- Testing of inorganic or organic contaminants
- Slightly more complicated and expensive to complete
- Usually takes more time



Case Study

Part 1 – Bench-Scale Testing

Approach: Static Batch and
Flow-Through Column Reactors

Objective: Evaluate the feasibility of
removing various heavy metals from ARD
and other impacted groundwaters




Case Study Part 1 – Bench-Scale Methodology

- Obtain samples of impacted groundwater from sites
- Set-up static batch reactors with different reactive media
- Assess performance
- Set-up multiple flow-through column reactors with preferred reactive media
- Record flow rates (contact times) and analyze effluent
- Interactively adjust reactive media composition to provide better performance and longevity



Case Study Part 1 – Bench-Scale Results

Examples of Heavy Metal Reductions in Groundwater Using ZVI (some pH buffered)



Case Study Part 1 – Bench-Scale Results

Parameter	Percent Reductions Achieved
Antimony	>99%
Arsenic	>99% to >99.9%
Cadmium	>99.99%
Chromium	>95 to >99.999%
Cobalt	>99.9%
Hex. Chromium	>99% to >99.99%
Manganese	>99%
Nickel	>99%
Zinc	>99.99%

Bench-scale testing can be (and has been) used to demonstrate that heavy metal impacts from MN/ARD & other industrial sites can be passively treated over the long-term



Detailed Design & Sensitivity Analysis



Detailed Design & Sensitivity Analysis

Detailed Design:

- Profile PRB alignment – chemical & physical
- Contaminant mass flux across PRB
- Required contact time for percent reductions needed (e.g. half lives)
- Lifetime demand of remedial amendment(s)
- Minimum density required for contact
- Apply safety factors (typically 100%)

Sensitivity Analysis:

- Effect of variability / uncertainties (in order of importance):
 - Contaminant concentrations in soil and groundwater
 - Hydraulic conductivity
 - Hydraulic gradient
 - Formation porosity



Installation Techniques



Installation Techniques – Excavation




Installation Techniques – Overburden Injection




Installation Techniques – Overburden Injection

The Goal:

- Uniform Distribution
- Contact between remedial amendment and contaminants




Plan View



Profile View

Installation Techniques – Bedrock Injection



Case Study

Part 2 – Full-Scale Installation

Approach: Injected and
Funnel & Gate Trenched PRBs

Objective: Remediate a plume of high
concentration arsenic in groundwater
from migrating to an adjacent water body




Case Study Part 2 – Full-Scale PRB Installation



- Former site of lead smelting and leather tanning operations
- Significant soil and groundwater impacts from arsenic
- Concern over discharge of impacted groundwater to adjacent river

Case Study Part 2 – Site Background



- Arsenic in soil >16,000 ppm
- Soils were leachate toxic (hazardous) waste
- Arsenic in groundwater >200,000 ppb in source area
- Original RFP was for a pump & treat (i.e., active) system

Case Study Part 2 – PRB Conceptual Design



Alternate proposal for a “funnel & gate” cut and fill ZVI PRB with injected ZVI PRB as a back-up

Case Study Part 2 – Full-Scale Installation – Injection



- Injected PRB first installed near shoreline (too close to excavate)
- Injected micro-scale ZVI in a slurry using Geoprobe
- Then trenched and emplaced macro-scale ZVI mixed with concrete sand into main “funnel & gate” PRB

Case Study Part 2 – Full-Scale Installation – Trenching

Line of temporary
points
for injected PRB


Excavation for
“cut & fill” PRB



Main “funnel & gate” direct place ZVI PRB installation




Case Study Part 2 – Groundwater Flow Pattern




Case Study Part 2 – Performance Monitoring – Locations

Cross Section




Case Study Part 2 – Performance Monitoring – Observations

Arsenic Concentrations (ug/L) vs Time



Case Study Part 2 – Performance Monitoring – Observations

Arsenic Concentrations (ug/L) vs Time



Case Study Part 2 – Full-Scale Results

- Passive PRB and source area capping proposed as an alternate, more cost-effective and sustainable solution to requested pump & treat system
- Two-stage PRB installed:
 - Injected ZVI PRB close to the shoreline as a back-up
 - Main funnel and gate trenched PRB installed further inland
- Full-scale implementation completed in 2014 with seven years of post-installation performance monitoring data available:
 - As concentrations in source area remain high ($>100,000$ ug/L)
 - Downgradient well has sustained As concentrations much lower ($\sim 20,000$ ug/L) but suggests residual impacts likely downgradient of first PRB
 - Additional treatment of groundwater will occur from second PRB before discharge to river
 - $\sim 99.98\%$ reduction of As in groundwater within PRB



QA/QC Testing



Quality Assurance / Quality Control – Old School




- Samples of ZVI / sand mixture collected from each batch mixed for magnetic separation testing
- Post-installation boreholes drilled through reactive media portion of PRB for magnetic separation testing
- Results compared to target concentrations (e.g. 30% wt./wt.)
- Low accuracy; subject to human error

Date	Batch	ZVI (%)
26/04/2016	1	32.3%
26/04/2016	2	31.9%
26/04/2016	3	31.5%
28/04/2016	4	33.7%
28/04/2016	5	34.2%
Average		32.7%

QA/QC Testing – New & Improved



Magnetic Susceptibility
Testing for ZVI content



QA/QC Testing – Performance Monitoring



Ultimate PRB Validation:

- Sampling & laboratory analysis of upgradient vs downgradient heavy metal concentrations
- Monitoring expected changes in geochemistry (pH, ORP, etc.)
- Monitoring consistency in treatment over time

Closing Thoughts



Closing Thoughts – PRBs for ML/ARD

Applicability of PRBs to ML/ARD:

- Well-proven technology with a long track record of success
- Suitable for most heavy metals common in ML/ARD at mining & industrial sites
- Bench-scale testing for site-specific applicability & to optimize remedial amendments
- Flexible application / installation methods
- Excellent Risk Management option – plume containment & property boundary control
- Very long lasting (years to decades)
- Relatively inexpensive and sustainable (passive)



Closing Thoughts – PRB Design & Installation


Why the Design, Installation & Performance of PRBs is Better than Ever:

- Existing site characterization data (CSM) is reviewed & validated
- Desktop modeling & preliminary design is completed
- Significant data gaps / unacceptable uncertainties are identified
- Additional site data collected, if needed (HRSC, k testing) to resolve
- Potentially appropriate remedial amendment(s) selected
- Bench-scale testing completed to assess site-specific response
- Detailed design & sensitivity analysis completed; safety factors applied
- Robust QA/QC program to ensure field installation is as per design
- Results in a long-lasting, sustainable PRB that has been properly designed using defensible scientific and engineering principals & is tailored to the site



Old School way

Where we are today



(The Evolution of PRB Design, Installation and Verification)

Questions?

Thank You for Your Time!

Kevin French, B.A.Sc., P.Eng.

Vertex Environmental Inc.

(519) 404-5442

kevinf@vertexenvironmental.ca

www.vertexenvironmental.ca

